

# Power Supplies



## Small Form Factor Power Supplies



Model Names	1757000160G 1757000229G	OP-20PZE	1757000209G
Wattage	1U, 300 W	200 W	1U, 150 W
Input Range	100 ~ 240 V <sub>AC</sub> 63 ~ 47 Hz 6 ~ 3 A	100 ~ 240 V <sub>AC</sub> 63 ~ 47 Hz 4 ~ 2 A	100 ~ 240 V <sub>AC</sub> 63 ~ 47 Hz 4 ~ 2 A
Outputs	+5 V @ 25 A (3 A min) +3.3 V @ 14 A (1 A min) +12 V @ 16 A (2 A min) -12 V @ 1 A -5 V @ 0.5 A +5 Vsb @ 2 A	+5 V @ 16 A (2 A min) +12 V @ 9 A (1 A min) -12 V @ 0.7 A -5 V @ 0.2 A	+5 V @ 14 A (2 A min) +3.3 V @ 10 A (1 A min) +12 V @ 6 A (1 A min) -12 V @ 0.8 A -5 V @ 0.5 A +5 Vsb @ 1.5 A
Power Module PN	-	-	-
MTBF (hrs)	100,000	84,000	84,000
Dimension (H x W x D, mm)	40 x 100 x 205	40 x 100 x 190	40 x 100 x 190
Safety	UL, TUV, CB, CCC	UL, TUV, CB, CCC	UL, TUV, CB, CCC
Compatible with Advantech Chassis	1757000160G: IPC-603MB, IPC-6806W 1757000229G: IPC-5120, IPC-7120	IPC-6806	IPC-6806S



Model Names	1757920011G	1757000170G
Wattage	200 W	150 W
Input Range	100 ~ 240 V <sub>AC</sub> 63 ~ 47 Hz 4 ~ 2 A	115 ~ 230 V <sub>AC</sub> 63 ~ 47 Hz 4 ~ 2 A
Outputs	+5 V @ 16 A (2 A min) +3.3 V @ 14 A (1 A min) +12 V @ 9 A (1 A min) -12 V @ 0.7 A -5 V @ 0.2 A +5 Vsb @ 1.5 A	+5 V @ 15 A (1 A min) +3.3 V @ 17 A (0.5 A min) +12 V @ 8 A (2 A min) -12 V @ 0.8 A +5 Vsb @ 2 A
Power Module PN	-	-
MTBF (hrs)	84,000	100,000
Dimension (H x W x D, mm)	40 x 100 x 190	63.5 x 100 x 125
Safety	UL, TUV, CB, CCC	UL, TUV, CB
Compatible with Advantech Chassis	IPC-6806 by OEM inquiry	IPC-644